


GYRO SERIES CUBE 2


- lumen talk
- Twin gimbal downlight with gyroscopic movement
- Die-cast construction
- Lockable tilt mechanism
- AlphaLED Fast Fix mechanism
- Supplied with pre-wired remote non-dimming driver
- Trimless option with skim bead
- Glare control accessories available



TRIMLESS
Product Code **2T**

Accessories


To order, use the following suffix



- /SN Snoot
- /HL Honeycomb louvre
- /SL Softening Lens
- /CG Clear Glass
- /WB White inner body and gyro rings

Snoot & Honeycomb

Calculations for x1 optic



PRODUCT CODE

Please refer to following page for product exceptions

Lumen Output:

- (05) 500 lm
- (07) 700 lm
- (10) 1000 lm
- (13) 1300 lm
- (20) 2000 lm
- (30) 3000 lm

Colour Temps:

- (27) 2700K
- (30) 3000K
- (35) 3500K
- (40) 4000K

Colour Rendering:

- (V8) Vibrancy 80
- (V9) Vibrancy 98
- (80) CRI 80+
- (98) CRI 98
- (B9) Beauty


Beam Angles:

- (S) Spot: 10°
- (N) Narrow: 28°
- (M) Medium: 40°
- (W) Wide: 60°

Colour:

- (W) White
- (N) Nickel Satin
- (B) Black
- (X) Trimless

2C



- Options: _____
- Dimming:**
- /DT Trailing Edge
 - /DL Leading Edge
 - /DD DALI
 - /DA Analogue (1-10V)
 - /LT Lumentalk
 - /M3 3Hrs Maintained
 - /ST Self Test
 - /DE DALI Emergency

For full list of options see page 2.

Availability

LED Modules
 CRI80 / Vibrancy 80: Standard delivery.
 CRI98 / Vibrancy 98 / Beauty: Extended delivery times may apply, please contact sales.
 Future Xicato LED modules: Available via special order. Extended delivery times may apply, please contact sales.

Colour
 White: Standard delivery.
 Nickel Satin: Standard delivery.
 Black: Standard delivery.

Product Options

GYRO SERIES CUBE 2

	CRI 80				CRI 98				VIB 80				VIB 98				BEAUTY				
Beam Angle	700lm	1000lm	1300lm	2000lm	3000lm	700lm	1000lm	1300lm	2000lm	3000lm	700lm	1000lm	1300lm	2000lm	3000lm	700lm	1000lm	1300lm	2000lm		
Beam Angle																					
Spot: 10°	✓	✓	✓	—	—	✓	✓	—	—	✓	✓	✓	✓	—	✓	✓	—	—	—	—	—
Narrow: 20°	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Medium: 40°	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Wide: 60°	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Colour Temps																					
2200°K	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
2700°K	✓	✓	✓	✓	✓	✓	✓	✓	✓	—	—	—	—	—	—	—	—	✓	✓	✓	
3000°K	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	—	—	—	
3500°K	✓	✓	✓	✓	✓	✓	✓	✓	✓	—	—	—	—	—	—	—	—	—	—	—	
4000°K	✓	✓	✓	✓	✓	✓	✓	✓	✓	—	—	—	—	—	—	—	—	—	—	—	
Body Colour																					
White	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Black	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Satin Nickel	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Grey	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
Dimming Options																					
Standard	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
/DT Trailing Edge	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	○	✓	✓	✓	
/DL Leading Edge	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	○	✓	✓	✓	
/DD DALI	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
/DA Analogue (1-10V)	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
/DS DSI	—	●	●	✓	✓	—	✓	—	—	—	●	●	✓	—	✓	—	—	—	✓	—	
/SD Switch Dim	—	●	●	✓	✓	—	✓	—	—	—	●	●	✓	—	✓	—	—	—	✓	—	
/DX DMX	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
/AP Analogue Pro	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
/DP DALI Pro	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
/UV Universal Voltage	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
/RD Rotary Dimming	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
Emergency Options																					
/M3 3Hrs Maintained	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
/ST Self Test	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
/DE DALI Emergency	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Accessories																					
/P Custom Colour	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
/AB Astral Bezel	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
/AW White Front Ring	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
/BD Barn Doors	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
/BF Baffle	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
/CG Clear Glass	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
/CG w/c Clear Glass (With Clip)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
/GR Glass Ring	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
/HL Honeycomb Louvre	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
/HL w/c Honeycomb Louvre (With Clip)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
/RG Ribbed Spreading Glass	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
/RG w/c Ribbed Spreading Glass (With Clip)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
/SL Softening Lens	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
/S w/c Softening Lens (With Clip)	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
/SN Snoot	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
/WB White Inner Body With Gyro Rings	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	
Regional Driver Spec																					
/BIS	Regional driver spec for India, beam angles will vary. Please contact sales team for more information.																				

Key

- ✓ Option Available
- Only available with spot/narrow optics
- Only available with medium/wide optics
- Option not available